

PRODUCT DESCRIPTION

AGH Paints Procoat primer is a acrylic Interior Wall Primer, a water-based wall coating suitable for application of interiors as an undercoat to interior emulsions. It provides excellent opacity and whiteness, Improves appearance of top coat. It does not chalk and should be applied on adequately cured plaster. It also provides excellent adhesion to top coat and prevents peeling off of top coat emulsion.

PERFORMANCE FEATURES & BENEFITS:



SURFACE PREPARATION

PLASTER -New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

CLEANING -Ensure that surface is completely free from all dirt, loosely held plaster, powdery residue, oil, grease or any other contamination. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water. One coat of Bio wash is recommended to prevent further growth of algae, fungus or moss.

FILLING FOR CRACKS For filling cracks up to 3mm use any best Crack Seal.

FILLING FOR HOLES & DENTS In case of dents and holes use putty or white cement.

RECOMMENDED SYSTEM FOR APPLICATION:

Primer Application:

Application can be done with brush, roller & spray.

After 24 hours of putty application, apply two coats of Pro oat Interior primer. Allow overnight drying time between the two coats. After the 2nd coat of Primer, the surface should be dry cut with finer grit sandpaper before application of the Top Coat. Before painting the following things should be checked thoroughly:

1. Moisture content of the wall (Ideal condition- below 12%)
2. pH value of the wall surface (Ideal condition-below 11)

Technical Data –

Thinning	Thin 60- 70 % by volume with water
Stability of thinned paint	Use within 24 hr.
Coverage/lit.	250-280 sq. ft
Drying time	Surface dry time 30 min
Flash point	NA
Sheen level	Matt

**Actual covering capacity may vary depending upon the method & condition of application.

Storage:

Store in a cool dry place. Keep away from source of ignition.

Keep container tightly closed, out of children's reach and away from foodstuff.

Disposal:

Do not pour left over paint down the drain or any watercourse. Dispose in accordance with local regulation.

Safety & Precaution:

Ensure good ventilation during application and drying of paint.

Wear protective clothes and gloves.

Smoking is prohibited while painting.

Avoid inhaling the vapor. Wear suitable dust nose pad when rubbing the surface.

Wear eye protector during application. In case of contact with eyes, rinse immediately with plenty of water.

POST APPLICATION INSTRUCTIONS

For the best performance of the paint, ensure proper washing and cleaning of all algae and fungal growth at regular intervals of 6 months.

DISCLAIMER**SAFETY FEATURES**

Non Flammable.

**PACK SIZE**

4L, 10L, 20 L & 50L

Shelf Life : 3 Years from the date of Manufacturing.

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products, therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement, prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.

