



OPULENCE PREMIUM LUXURY EMULSION



PRODUCT DESCRIPTION

Opulence, a water based luxury emulsion gives your walls an exquisite look with clear colors & a rich smooth finish. It stays awe inspiring for years with excellent washability, **silky glowing appearance** & superior stain resistance.

PERFORMANCE FEATURES & BENEFITS



SURFACE PREPARATION

1. Rub the surface using a suitable abrasive paper and wipe it off to ensure that the surface is clean, dry and free from dirt, grease, wax or any other defective or poorly adhering material.
2. Treat fungus affected areas using any fungicidal Solution and allow it to react for 6-8 h.
3. Apply a coat of AGH Procoat Primer, followed by Wall Putty · level and smoothen the surface.
4. Sand the surface with Emery paper 180 & wipe clean.
5. Apply another coat of Procoat primer on puttied areas.
6. Sand the surface with Emery paper 320 & clean the surface with cloth before painting.
7. Finally, apply two to three coats of AGH Vastu Opulence Luxury Emulsion as per recommended thinning. Dark shades may require additional coat for hiding.

RECOMMENDED USAGE

AGH Vastu Opulence luxury emulsion is designed for application on new as well as previously painted interior surfaces such as plaster, brickwork, cement rendering, concrete, hard boards, etc.

APPLICATION (For New Masonry Surfaces)

1. Primer** (1 coat), Dry[#] in 4-6 h.
2. Putty[#], Dry in 6-8 h.
3. Primer** (1 coat), Dry[#] in 4-6 h.
4. Top coat Opulence (2-3 coats), Dry min. 3-4 h in between coats.

Sand the surface with Emery paper and clean before application of subsequent coat.

**AGH VASTU Procoat Primer (Water thinnable)

**Any Wall putty application.

Minimum 4-6 h for water thinnable Primer.

For Repainting on Smooth Lime/Distemper/Emulsion/Enamel Masonry Surfaces skip steps 1 & 2 and start with step 3.

PRECAUTIONS

1. Refer MSDS for "AGH Vastu Opulence Luxury Emulsion" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection is dangerous. In either case, move to fresh air & consult a medical practitioner.
6. Do not apply when ambient temperature might drop to a level below 10°C within 4 h of application.
7. New plasters should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Stir the tinted paint well, after tinting & before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipment like rubber or polythene gloves, safety goggles / glasses & face mask.

TECHNICAL DATA

Teflon Surface Protector

Provides a durable protective layer

Stain Resistance

Resists both hydrophobic and hydrophilic stains

Water Thinning

40 -50% by weight

Recoating

Min.3 -4 hr@ Room Temp.

Washability

High washable & stain resistance

Durability

10 years performance warranty

Luxurious Finish

Offers a silky, glowing appearance

Excellent Coverage

Ensures superior hiding Power /160 -180 sq. ft./lit.



***Actual coverage may vary depending on method & condition of application, surface roughness & surface.

POST APPLICATION INSTRUCTIONS

For removing stains, sponge clean with a mild soap solution and wipe clean. Please allow 2 weeks of drying time to freshly painted wall for it to be ready for stain removal / cleaning.

SAFETY FEATURES

Non-Flammable

PACK SIZE

1 L, 4 L, 10 L & 20 L.

SHADE RANGE

1300+ shades available

SHELF LIFE

3 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct sunlight and excessive heat.

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore, actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The Company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.

